



KODAK PROFESSIONAL

Satin Photo Paper, 270gsm

Produce high-quality imagery on this environmentally-friendly photo paper

High-quality reproductions at an economical price

KODAK PROFESSIONAL Satin Photo Paper, 270gsm, is a satin finish, resin-coated photo paper with a weight (270 gsm) and thickness (10.5 mil) comparable to other popular inkjet photo papers but at an economical price.

Accurate reproduction on a satin finish

This photo paper produces sharp, detailed imagery for professional portrait, wedding, event, and advertising photographers who want the lower glare of a traditional smooth luster. The paper is sufficiently water-resistant to avoid damage during everyday use and has a wide color gamut and high white point for contrast.

FSC®-certified

Meet environmental objectives with this FSC®-certified paper.

FEATURES:

- Economical solution for production-type photographic applications
- Wide color gamut, enhanced density, and sharpness
- FSC®-certified

APPLICATIONS:

- Photographic prints
- Fine art reproductions
- Posters
- Interior Décor

US Size	Euro Size	Quantity	SKU
24" x 100'	61,0 cm x 30,5 m	1 Roll	KPROSPP24100
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPROSPP36100
44" x 100'	111,7 cm x 30,5 m	1 Roll	KPROSPP44100
60" x 100'	162,5 cm x 30,5 m	1 Roll	KPROSPP60100



KODAK PROFESSIONAL

Satin Photo Paper, 270gsm

Properties	Specifications
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks
Material	Resin-coated (RC) photo paper
Weight (gsm)	270g
Thickness (μ)	10.5 mils / 254 microns
Finish	Satin
Opacity	> 86
CIE Whiteness	> 145
Core Size	3-in Core
Print Sides	One-sided
Environmental	FSC®-certified
Unit	1 Roll
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Finishing/Post Processing	Pressure-sensitive vinyl laminates with UV inhibitors can be applied to increase the fade and abrasion resistance of the image. Before applying the laminate, allow the image to dry for 24 hours. Residual solvent trapped beneath a laminate as a result of insufficient dry time can cause color shifts
Software Settings	The coating on this product is engineered for better than 300% ink coverage. A photo luster, satin or semi-gloss setting is the recommended starting point. However, we recommend a custom ICC profile for optimal results. Please refer to www.lexjet.com for starting-point ICC profiles for some printers.
Optimal Print Environment	70° F (21° C), 50% R.H
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet-coated materials. Rolls of LexJet film are supplied with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.



AMS: 888-893-4668
EMEA: +34 935 479 700
APJ: +61 2 8038 5013

KODAKWFMedia.com



The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group

