QUALITY, QUANTITY, SPEED.

Production Redefined

imagePROGRAF
GP-6600S

Specifications

Print Head
PF-10

Number of Nozzles
(MBK/C/M/Y/O: 1,536 nozzles x2 BK/GY: 1,536 nozzles x1): 18,432 nozzles

Droplet Size
Minimum 4 pl per color

Ink Type
MBK, BK, C, M, Y, GY, O

Ink Tank
Shipped with printer: 330 ml Tank
Replacement: 160 ml PFI-3100 (BK, C, M, Y, GY), 160 ml PFI-2100 (MBK, O), 330 ml PFI-3300 (BK, C, M, Y, GY), 330 ml PFI-2300 (MBK, O), 700 ml PFI-3700 (BK, C, M, Y, GY), 700 ml PFI-2700 (MBK, O)

Printer RAM
Standard Memory: 3 GB
Hard Disk: 500 GB

Media Feed
Front-Loading Roll Feed: Two* Rolls, Front Output

Media Width
Roll Feed: 6" - 60" (152.4 mm - 1,524 mm)
Cut Sheet: 6" - 60" (152.4 mm - 1,524 mm)

Media Cutter
Automatic horizontal cutting (Rotary cutter): standard

Media Thickness
0.002" - 0.03" (0.07 mm - 0.8 mm)

Media Core Sizes
2" Core Standard. 2"/3" Core Roll Holder Set (RH2-66)

Maximum Roll Outer Diameter
6.7" or less (170 mm or less)

Media Output
Catch Basket

Printing Software Utilities
Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon Print Service, Professional Print & Layout, Quick Utility Toolbox

Operating System
Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), MacOS v10.15.7- MacOS 13

Print Language
Printer: SGRaster (Swift Graphic Raster), PDF, JPEG

Interface
Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g /n) ▪

Power Supply
AC 100 – 240V (50 – 60 Hz)

Power Consumption
Max: Approx 94W
Standby: Approx. 1.7W
Power Off: Approx 0.1W

Certifications
Environmental Certifications
ENERGY STAR® (Worldwide), EPEAT Gold

Operational Environment
Temperature: 59 – 86 °F (15 – 30 °C)
Relative Humidity: 10 – 80% (Non Condensation)

Printer Dimensions (W x D x H) and Weight
(with stand and basket open) 78.7" x 38.7" x 46", 372.6 lbs

Package Dimensions (W x D x H) and Weight
(main unit with pallet) 87.7" x 36.0" x 40.4", 480.6 lbs
Multifunction Roll Unit (physically strapped to printer) 84.0" x 22.1" x 18.1", 92.6 lbs

Options
• 2"/3" Roll Holder Set (RH2-66)
User Replaceable Items
• Ink Tank: PFI-3100 (160 ml)/PFI-3300 (330 ml)/PFI-3700 (700 ml) BK, C, M, Y, GY, 160 ml PFI-2100/330 ml PFI-2300/700 ml PFI-2700: MBK, O
• Print Head (PF-10)
• Maintenance Cartridge (MC-30)
• Cutter Blade (CT-07)

What's In The Box
Printer, Multifunction Roll Unit, 330 ml Starter Ink Tanks, 1 Print Head, Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, One Year Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)

▪ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

★ If Multifunction Roll is used.

usa.canon.com/imagePROGRAF