

EcoVantage® 190 is a 100% PVC-free and phthalate-free material for outdoor advertising. The material provides an excellent option for a lightweight, sustainable substrate and can be used for banners, display framing systems, point-of-sale and more. EcoVantage® 190 is recyclable under code nr. 1 (PET) and is compatible with solvent, eco-solvent, UV, Latex, and screen printing. Available in widths of 126" and 196".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Composition	DIN ISO 2076	100% Polyester	
Total Weight	DIN EN ISO 2286-2	200 g/m ²	5.9 oz./yd ²
Thickness		0.24mm	9.44 mil
Tensile Strength	DIN EN ISO 1421-1	150 x 140 daN/5 cm	171.3 x 159.8 lbs./inch
Tear Strength	DIN 53363	25 x 20 daN	56 x 45 lbf
Welding	Weldable with welding aide		
Fire Resitance	NFPA 701		

Applications

	Indoor	Outdoor	POS	Retail Applications	Banners	Display Frame Systems
Applications	■	■	■	■	■	■

Ink Printability

Available Sizes

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

Metric (m)	English (inches)
3.2, 5.0	126, 196

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)