



KODAK PROFESSIONAL

Inkjet Photo Paper, Matte / 230g

Ideal paper for high-resolution output

High-resolution output

This is the ideal workhorse photo paper for accurate color reproduction and high-resolution output.

Acid-free

KODAK PROFESSIONAL Inkjet Photo Paper, Matte / 230g is a smooth neutral-white matte finish that is acid-free for long-lasting prints with pigmented inks.

Instant-dry

Its instant-dry coating prevents smudging and fingerprints, providing hassle-free print production.

FSC®-certified

Meet environmental objectives with this FSC®-certified paper.

APPLICATIONS:

- Fine art and photographic reproduction
- Wedding, portrait, landscape and exhibition photography
- Home décor

FEATURES:

- Instant-dry coating
- Acid-free for longer lasting images
- Smooth, matte finish
- Compatible with both dye and pigment inks
- FSC®-certified paper

US Size	Euro Size	Quantity	SKU
8.5" x 11"	20,08 cm x 29,72 cm	50 Sheets	KPRO8511M
13" x 19"	33,02 cm x 48,26 cm	20 Sheets	KPRO1319M
*(A4) 8.3" x 11.7"	20,08 cm x 29,72 cm	50 Sheets	KPROA4M
*(A3+) 13" x 19"	33,02 cm x 48,26 cm	20 Sheets	KPROA3+M
10" x 100'	25,4 cm x 30,5 m	1 Roll	KPRO10M
17" x 100'	43,2 cm x 30,5 m	1 Roll	KPRO17M
24" x 100'	61,0 cm x 30,5 m	1 Roll	KPRO24M
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPRO36M
42" x 100'	106,7 cm x 30,5 m	1 Roll	KPRO42M
44" x 100'	111,8 cm x 30,5 m	1 Roll	KPRO44M
60" x 100'	152,4 cm x 30,5 m	1 Roll	KPRO60M



KODAK PROFESSIONAL

Inkjet Photo Paper Matte / 230g

Properties	Specifications
Material	61# matte, neutral white paper
Gauge	9.5 mil 230 gsm +/-5
Gloss Level	> 98
Whiteness	>95
Environmental	FSC®-certified paper
Printer/Ink Compatibility	Dye/pigment
Software Setting	The bond or uncoated paper setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to www.brandmanagementgroup.com/profiles for starting-point ICC profiles
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Finishing/Post Processing	No post processing or finishing is required. A clear fixative may be applied to enhance certain areas of the print. We recommend waiting 24 hours before placing the print behind glass.
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface of the paper. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of Kodak paper and film are supplied with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.
Optimal Service Environment	72° F (21° C), 50% R.H. For end use: 0-300° F



The mark of
responsible forestry

BMG BRANDmanagementGROUP

AMS: 888-893-4668

EMEA: +34 935 479 700

APJ: +61 2 8038 5013

KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2022, Brand Management Group

