Mid States Graphics

Premium Display Film / ES

7 mil Satin biaxially oriented polypropylene film with a low tack repositionable adhesive.

Features and Benefits:

- The release liner is polyester textured to ensure air release during application, which will eliminate bubbles and wrinkles.
- It is an ecologically friendly alternative to PVC.
- Tear Resistant

Part Number	Size	Core	Weight
ES-PDF36100	36”x100’	3”	17 lbs.
ES-PDF42100	42”x100’	3”	20 lbs.
ES-PDF50100	50”x100’	3”	24 lbs.
ES-PDF3610	36”x10’ Test Roll	3”	2 lbs.

Cautions:

- Always wait at least one hour after printing before attempting to mount graphic.
- Surface must be smooth, clean, dry, and have no bumps, or defects.
- Keep a roller handy during application.
- Before applying on freshly painted walls allow 4 weeks for the paint to cure before application.
- DO NOT stretch graphic during application.
- DO NOT use application fluids or liquids during application process.
- DO NOT use tapes.
- Always test cutter force/pressure before performing contour cut.

Physical Properties:

Parameter	Value
Thickness	7 mil
Base Weight	250 gsm
Color	White

Applications:

- ✓ Window Graphics
- ✓ Wall Graphics
- ✓ Temporary Use on Vehicles
- ✓ Prototyping
- ✓ Adheres to Most Non-Porous Surfaces

Compatibility: * Eco Sol * Solvent * UV * Latex

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

Mid States Graphics, LTD
1700 Drake Ct
Hanover Park, IL 60133
T: 630-837-8571
Sales@myproofline.com
www.midstatesgraphicsltd.com