


CLASSIC VINYL

GENERAL USE
CALENDERED VINYL



Nekoosa's Classic Vinyl product portfolio is intended for interior and exterior point-of-purchase graphic applications.

Classic Vinyls

Suitable for indoor and outdoor applications (<3 years outdoors)

Grades with removable adhesive will remove cleanly from surfaces within 1 year

Matte, gloss or clear finishes

Clear or gray block-out, permanent or removable pressure sensitive adhesive

Air-egress options available

Layflat 90# release liner, superior for printing with latex and UV wide format printers

Easy installation onto flat and simple curves without rivets

Print Compatibility: Wide Format (Solvent, Eco-Solvent, Latex and UV),
Offset (Conventional and UV), HP Indigo and Screen

Applications

Banner Graphics

Cut Lettering

Decals

Point-of-Purchase Signage

Bumper Stickers

Fleet Markings

Name Plates

In-Store Promotions

SCAN HERE FOR
FREE SAMPLES ▶



Certified for
HP Indigo



800.826.4886 | cs@nekoosa.com

NEKOOSA.COM

03.06.25 | M1580-OV

CLASSIC VINYL

GENERAL USE
CALENDERED VINYL



STOCKED PRODUCTS ▶

	Finish/Color	SKU #	Size	Film Thickness	Adhesive	Liner	Rolls/Carton		
Wide Format									
	Gloss White	SPM390G5450	54" x 50 yd	3 mil	Gray Permanent	90# Layflat	1		
		SPM390GWF5450	54" x 50 yd	3 mil	Permanent	90# Layflat	1		
		SPM390GWR/GR5450	54" x 50 yd	3 mil	Gray Removable	90# Layflat	1		
		SPM490FWP5450	54" x 50 yd	4 mil	Permanent	90# Layflat	1		
	Matte White	SPM490FWR5450	54" x 50 yd	4 mil	Removable	90# Layflat	1		
		SPM490FWP/GR5450	54" x 50 yd	4 mil	Gray Permanent	90# Layflat	1		
		SPM490FWR/GR5450	54" x 50 yd	4 mil	Gray Removable	90# Layflat	1		
		SPE490FWP/GR5450	54" x 50 yd	4 mil	Gray Permanent	90# Layflat Air-Egress	1		
		SPE490FWR/GR5450	54" x 50 yd	4 mil	Gray Removable	90# Layflat Air-Egress	1		
		Gloss Clear	SPM400C450	54" x 50 yd	4 mil	Permanent	90# Layflat	1	
	Finish/Color	SKU #	Size	Film Thickness	Adhesive	Liner	GSM	M. Wgt	Sheets/Carton
HP Indigo									
	Matte White	SPM400FWPIN1218	12" x 18"	4 mil	Permanent	90# Layflat	300	100	400
		SPM400FWPIN1319	13" x 19"	4 mil	Permanent	90# Layflat	300	110	400
	Gloss Clear	SPM400FCPIN1218	12" x 18"	4 mil	Permanent	90# Layflat	290	95	400
		SPM400FCPIN1319	13" x 19"	4 mil	Permanent	90# Layflat	290	100	400

Certified for
HP Indigo

CLASSIC VINYL

GENERAL USE
CALENDERED VINYL



CUSTOM SIZE OFFERING ►

	Finish/Color	SKU #	Size (width)	Film Thickness	Adhesive	Liner	Wgt/MSI
HP Indigo	Matte White	SPM400FWPIN	54"	4 mil	Permanent	90# Layflat	300
	Gloss Clear	SPM400FCPIN	54"	4 mil	Permanent	90# Layflat	290

Custom Size Offering: Custom sizes for the HP Indigo 10,000/12,000 available upon request.

	Finish/Color	SKU #	Size (width)	Film Thickness	Adhesive	Liner	Wgt/MSI
Non Top-Coated - UV Offset & Screen	Gloss White	CV300GWF/GR	54"	4 mil	Gray Permanent	90# Layflat	.50#
		CV300GWF	54"	4 mil	Permanent	90# Layflat	.50#
		CV300GWR/GR	54"	4 mil	Gray Removable	90# Layflat	.50#
	Matte White	CV400FW/P	54"/60"	4 mil	Permanent	90# Layflat	.50#
		CV400FW/R	54"	4 mil	Removable	90# Layflat	.50#
		CV400FWP/GR	54"	4 mil	Gray Permanent	90# Layflat	.50#
		CV400FWR/GR	54"	4 mil	Gray Removable	90# Layflat	.50#
	Gloss Clear	CV400C/P	54"	4 mil	Permanent	90# Layflat	.50#
		CV400C/R	54"	4 mil	Removable	90# Layflat	.50#
	Matte Black	CV400FB	54"	4 mil	Permanent	90# Layflat	.50#

Custom Size Offering: Each product listed above can be custom converted into sheets or rolls to meet your specific requirements.

	Finish/Color	SKU #	Size (width)	Film Thickness	Adhesive	Liner	GSM
Top-Coated - Conventional Offset	Matte White	CV400FWP/TC	54"/60"	4 mil	Permanent	90# Layflat	.50#
		CV400FWR/TC	54"	4 mil	Removable	90# Layflat	.50#
		CV400FWP/TC/GR	54"	4 mil	Gray Permanent	90# Layflat	.50#
		CV400FWR/TC/GR	54"	4 mil	Gray Removable	90# Layflat	.50#
	Clear	CV400CP/TC	54"	4 mil	Permanent	90# Layflat	.50#

Custom Size Offering: Each product listed above can be custom converted into sheets or rolls to meet your specific requirements.

Certified for
HP Indigo

CLASSIC VINYL

GENERAL USE
CALENDERED VINYL

TECHNICAL DATA ▶

Wide Format ▶	SPM390G	SPM390GWF	SPM390GWR/GR	SPM490FWP	SPM490FWR	SPM490FWP/GR
HP Indigo ▶				SPM400FWPIN		
Custom ▶	CV300GWF/GR	CV300GWF	CV300GWR/GR	CV400FWP & CV400FWP/TC	CV400FW/R & CV400FWR/TC	CV400FWP/GR & CV400FWP/TC/GR
Physical Properties						
Finish	Gloss	Gloss	Gloss	Matte	Matte	Matte
Color	White	White	White	White	White	White
Adhesive	Permanent: Moderate Peel, Gray	Permanent: Moderate Peel, Clear	Removable: Moderate Peel, Gray	Permanent: Moderate Peel, Clear	Removable: Moderate Peel, Clear	Permanent: Moderate Peel, Gray
Film	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl
Liner	90# Layflat	90# Layflat	90# Layflat	90# Layflat	90# Layflat	90# Layflat
Opacity	99+%	92% minimum	99+%	92% minimum	92% minimum	100%
Gloss Level	80% typical	80% typical	80% typical	8% typical	8% typical	8% typical
Thickness	Film	3.0 ± 0.2 mil	3.0 ± 0.2 mil	3.2 ± 0.2 mil	3.2 ± 0.2 mil	3.2 ± 0.2 mil
	Film + Adhesive	4.0 ± 0.3 mil	4.0 ± 0.3 mil	4.2 ± 0.3 mil	4.2 ± 0.3 mil	4.2 ± 0.3 mil
	Total Thickness	10.5 ± 0.4 mil	10.5 ± 0.4 mil	10.5 ± 0.4 mil	10.7 ± 0.4 mil	10.7 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	40 oz/in minimum	45 oz/in minimum	10-14 oz/in typical	45 oz/in minimum	40 oz/in minimum
	SS 24 hr Room Temp Dwell	50 oz/in minimum	55 oz/in minimum	14-18 oz/in typical	55 oz/in minimum	50 oz/in minimum
Weight	Film + Adhesive	125-130 gsm	125-130 gsm	125-130 gsm	135-140 gsm	135-140 gsm
	Total Weight	275-285 gsm	265-275 gsm	275-285 gsm	280-290 gsm	290-300 gsm

Wide Format ▶	SPM490FWR/GR	SPE490FWP/GR	SPE490FWR/GR	SPM400C		
HP Indigo ▶				SPM400FCPIN		
Custom ▶	CV400FWR/GR & CV400FWR/TC/GR			CV400C/P & CV400CP/TC	CV400C/R	CV400B
Physical Properties						
Finish	Matte	Matte	Matte	Double Polished Gloss	Double Polished Gloss	Matte
Color	White	White	White	Clear	Clear	Black
Adhesive	Removable: Moderate Peel, Gray	Permanent: Moderate Peel, Gray	Removable: Moderate Peel, Gray	Permanent: High Peel, Clear	Removable: Moderate Peel, Clear	Permanent: Moderate Peel, Clear
Film	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl	Calendered Vinyl
Liner	90# Layflat	90# Air Egress	90# Air Egress	90# Layflat	90# Layflat	90# Layflat
Opacity	100%	100%	100%	15% maximum	15% maximum	99%
Gloss Level	8% typical	8% typical	8% typical	High Gloss	High Gloss	8% typical
Thickness	Film	3.2 ± 0.2 mil	3.2 ± 0.2 mil	3.1 ± 0.2 mil	3.1 ± 0.2 mil	3.1 ± 0.2 mil
	Film + Adhesive	4.2 ± 0.3 mil	4.2 ± 0.3 mil	4.2 ± 0.3 mil	4.1 ± 0.3 mil	4.1 ± 0.3 mil
	Total Thickness	10.7 ± 0.4 mil	11.8 ± 0.4 mil	11.8 ± 0.4 mil	10.6 ± 0.4 mil	10.6 ± 0.4 mil
Adhesion	SS 15 min Room Temp Dwell	10-14 oz/in typical	40 oz/in minimum	3-7 oz/in typical	65 oz/in minimum	4-8 oz/min
	SS 24 hr Room Temp Dwell	14-18 oz/in typical	50 oz/in minimum	13-17 oz/in typical	80 oz/in minimum	12-16 oz/in
Weight	Film + Adhesive	140-145 gsm	140-145 gsm	140-145 gsm	125-130 gsm	130-135 gsm
	Total Weight	290-300 gsm	300-310 gsm	300-310 gsm	290-300 gsm	270-280 gsm

	Permanent Water-Based	Removable Water-Based
Conditions for Use		
Shelf Life	1 year	1 year
Outdoor Durability	Up to 3 years	Up to 3 years
Min Application Temp	35° F (1.6° C)	40° F (4.4° C)
Service Temp Range	-20° to 150° F (-28.9° to 65.6° C)	-10° to 140° F (-23.3° to 60° C)
Solvent Resistance	Excellent	Excellent
Chemical Resistance	Excellent	Excellent

The information provided herein is correct to the best of Nekoosa's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.