

ProFlex Plus is a 13 oz. front-lit banner material. The material is compatible for use with solvent, eco-solvent, UV, Latex and screen printing and is available in a gloss or matte finish. The face-film provides exceptional ink receptivity and consistently prints from batch to batch. ProFlex Plus is available in widths up to 63”.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN60001	Polyester	Polyester
Yarn dtex		1000 x 1000 denier	
Total Weight	N/A	440 g/m <sup>2</sup>	13 oz.
Tensile Strength	ISO 13934-1 : 2013 CRE Strip Method	1303 x 965 N/5cm	148.80 x 110.20 lbs/in
Tear Strength (warp/weft)	ISO 13937-2:2000 CRE Single Tear method	70 x 60 N	15.74 x 13.49 lbf
Elongation	ISO 13934-1: 2013 CRE Strip Method	21 x 28 %	

### Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications	■	■	■	■	■	■	■

### Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

### Available Sizes

Metric (m)	English (inches)
Up to 3.2 m	Up to 63” in

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)